

METHODS FOR THE PREVENTION OF RADON EMISSIONS

10 CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to U.S. Provisional Patent Application Serial No. 60/113,091, filed December 21, 1998.

15 FIELD OF THE INVENTION

The present invention relates, in general, to methods for treating radioactive-containing waste materials. More specifically, the present invention relates to the prevention of radon emissions. More particularly, the present invention relates to the prevention of
20 radon emissions by encapsulating the radon in radon-generating waste matter using a chemical additive and by adjusting the shape of the carrier which stores the radon-generating waste matter.

BACKGROUND OF THE INVENTION

25 Radioactive materials are a major concern in the U.S. One of the more common radioactive materials is radon. Radon is a pervasive pollutant. Radon (Rn) is a naturally occurring element that is formed upon the radioactive decay of radium-226. Radon is tasteless, odorless and colorless. It exists as a gas in the form of
30 three natural isotopes - Rn-219, Rn-220, and Rn-222. The former two isotopes have half-lives of the order of seconds and thus are of little concern. However, Rn-222 decays in a slower process that is characterized by a considerably longer half-life of 3.82 days. Radon decay proceeds with emission of alpha particle radiation through a
35 series of solid, short-lived radioisotopes (e.g., polonium-218 and

polonium-214) that are collectively referred to as radon "daughters" or progeny.

These radon daughters, which are unstable isotopes in their own right, are responsible for most of the radiation dose associated with high radon levels in the air. Most radon gas that is inhaled is generally exhaled as well because its radioactive half-life is long as compared to the residence time of the gas in the lungs. However, the above-mentioned alpha-emitting polonium isotopes are solids rather than gases, and a fraction of these radon daughters are deposited on the surfaces of the airways deep in the lung when air is inhaled. The radon progeny deposited in this manner subsequently decay by emission of short-range but slow-moving and powerful alpha particles capable of damaging cells which they encounter. This alpha radiation dose is delivered to stem cells present in the epithelium that comprises the surface of the air passages in the lungs.

Radon gas in lungs is believed to be the second leading cause of lung cancer. Early United States Environmental Protection Agency (EPA) estimates indicated that in the United States alone 5,000 to 20,000 lung cancer deaths a year are attributable to "natural" radon from all sources, and more recent estimates tend to be larger, e.g., between 10,000 and 40,000 lung-cancer deaths each year. Extensive surveys of radon levels in homes and schools are under way at EPA's urging, based on its finding that some 10% of the nation's homes exceed its 4 picoCuries per liter (pCi/L) action level. Congress has recently identified a long-term goal of reducing indoor radon concentrations to typical levels in the outside environment (0.1-0.7 pCi/L), and EPA is publicizing radon mitigation measures and establishing the groundwork for eventual regulations dealing with allowable levels of radon in indoor air and drinking water.

The prior art has proposed several solutions in dealing with radon and radon emissions. Most of these solutions are directed to preventing radon emissions from entering an individual's home. One such solution has been to line the floor or ground below the home with a plastic covering designed to prevent radon from

entering through the ground or floor. However, these coverings only provide partial protection, and any slit or tear in the cover will permit the radon to enter the building.

5 U.S. Patent No. 5,399,603 discloses attempts to overcome these deficiencies by using a polymer sealant to coat the ground or floor. While these sealants are more effective at preventing radon emissions from penetrating into the home, they suffer some of the same problems that if part of the floor or ground is not coated, the radon emissions are still able to enter through these
10 openings.

Additionally, the above solutions are directed to preventing naturally occurring radon emissions from entering a home. Workers who work with radon-contaminated waste also need to be protected from the emissions. The choices available for
15 preventing radon emissions from radon-generating waste matter are much more limited. U.S. Patent Nos. 4,897,221 and 4,980,090 are directed to the treatment of radon-contaminated waste. These references admix the waste with a shielding material, such as ceramic, enamel, concrete or metal, and place the admixture into a
20 centrifuge to mix and encapsulate the waste within the shielding material. The encapsulated waste is then placed in a vault. However, the problems with this method are that the radon emissions are still able to escape the shielding material, which is the reason these wastes are placed into a vault.

25 Accordingly, what is needed is a method for preventing radon emissions from radon-generating waste such that workers who handle these types of waste will be protected from the radon. These methods would prevent radon emissions while obviating the need for protective vaults and would permit the wastes to be formed into
30 products that could be used without fear of harming members of the public.

SUMMARY OF THE INVENTION

35 The present invention is directed to methods for treating radioactive materials contained within a variety of different waste

materials. More specifically, the present invention is directed to the prevention of radon emissions wherein radon-emissions are minimized by admixing the radon-generating waste with a shielding material and then forming the admixture into geometric-shaped objects which minimize the surface area of the object with respect to the volume of the object, thereby reducing any radon emissions emanating from the object.

Additionally, the radon-generating waste may be admixed with a chemical additive which encapsulates the radon. Then, the encapsulated radon is admixed with a shielding material and formed into objects. These objects may further be shaped into geometric objects having a high ratio of volume to surface area to ensure that any radon which may not be encapsulated has less area from which to leave the object.

Finally, a polymer sealant optionally may be used to further prevent radon emissions from radon-generating waste which has either been encapsulated or formed into geometric shapes or both.

Accordingly it is an object of the present invention is to provide methods useful for treating waste material containing radioactive wastes.

It is another object of the present invention to provide a method of reducing radon emissions from radon-generating wastes by adding a chemical additive to the waste to encapsulate the radon prior to admixing the radon with a shielding material.

It is another object of the present invention to provide a method of reducing radon emissions from radon-generating wastes by adjusting the geometry of the shielding material into which the radon-generating waste is placed.

It is another object of the present invention to provide a method of reducing radon emissions from radon-generating wastes by both adding a chemical additive to the waste to encapsulate the radon and adjusting the geometry of the encapsulated waste.

It is another object of the present invention to provide a method of reducing radon emissions from radon-generating wastes

Ins
21

by further using a polymer sealant to prevent radon emissions from radon-generating wastes.

5 These and other objects, features and advantages of the present invention will become apparent after a review of the following detailed description of the disclosed embodiments and the appended claims.

DETAILED DESCRIPTION

10 Radioactive materials are located within a large variety of waste materials. As used herein, the term "radioactive" means any material that emits mass and energy during decay of the material. In particular, an example of a "radioactive material" is radium, which emits alpha particles and decays to radon. Radon is a common radioactive material and is found in a variety of different waste materials. These materials include, but are not limited to, 15 monazite, zircon, illmenite, phosphate, china-clay and thorium processing. Radon-generating waste materials should be treated before disposing of the materials to ensure that living things coming into contact with the waste materials will not suffer any radon emission exposure. 20

The present invention is directed to methods for treating radon-generating waste materials to reduce and substantially prevent radon emissions from escaping from the waste materials and endangering individuals handling the waste materials. The present invention sets forth several methods by which the waste materials 25 may be treated. One embodiment of the present invention involves admixing the waste material with a shielding material and then forming the admixture into geometric shapes having a high volume per unit surface area. Another embodiment of the present invention involves the use of chemical additives which encapsulate the radium and progenitors, thereby preventing radon emissions. Yet another embodiment of the present invention involves a combination of the 30 first two methods. Finally, polymer sealants may be used to further prevent radon emissions from escaping the waste materials.

In a first embodiment of the present invention, radon-generating material is admixed with a shielding material and the resulting admixture is then formed into geometric shapes having a high volume per unit of surface area.

5 As radium particles decay, they emit alpha particle radiation and radon. Radon, as a gas, can escape the waste material and become an airborne hazard. Therefore, shielding materials have been used wherein the shielding material help prevent radon from escaping the shielding material. However, these shielding materials
10 will still permit some radon to escape into the environment. The amount of radon escaping can be minimized by forming the admixture of the radon-generating waste material and the shielding material into geometric shapes that minimize surface area per unit volume. Therefore, the area through which the radon may pass is
15 minimized while still permitting large amounts of waste material to be treated.

In general, the shapes used should minimize surface area per unit volume. These shapes include, but are not limited to, generally spherical shapes and generally cubic shapes. However, any
20 geometric shape that minimizes the following equation will suffice in the present invention:

$$\text{volume}/(\text{surface area} \times 2)$$

25 As discussed above, the radon-generating material is preferably admixed with a shielding material prior to forming the material into geometric shapes. By "shielding material" it is meant any material that impedes or prevents radon from passing through the material. The shielding material is selected to provide a matrix within which the waste material is incorporated such that any radon
30 must first pass through the matrix of the shielding material before it can escape into the environment. The shielding material should also be selected based upon its ability to act as a barrier for radon. Examples of shielding materials useful in the present invention include, but are not limited to, ceramic, enamel, concrete or metal.

The radon-generating waste material and the shielding material may be admixed using any device capable of ensuring that the waste material will be thoroughly admixed and incorporated within the matrix of the shielding material. By "incorporated" it is meant that the waste material or polymer/waste material admixture is located within the matrix of cell walls of the shielding material such that the cell walls impede or prevent radon from passing through the cell walls or matrix of the shielding material. Examples of mixing devices useful in the present invention include, but are not limited to, centrifugal mixers and static mixers, among others.

The amount of shielding material used should be sufficient to fully incorporate the waste material within the matrix of the shielding material. In general, it is preferred that the ratio of the amount of shielding material to the amount of waste material is at least about 2 to 1. More preferably, the ratio is at least about 3 to 1 and even more preferably, the ratio is about 4 to 1. These ratios ensure that the waste material will be fully incorporated within the shielding material.

In a second embodiment of the present invention, a chemical additive is admixed with radon-generating waste material. The additive is chosen such that the additive encapsulates the radon, thereby preventing radon emissions from escaping from the waste material. The waste material may then be admixed with a shielding material to embed the radon-generating waste material within the matrix of the shielding material. The shielding material may then be disposed of by any process known in the art.

The additive materials useful in the present invention are selected to be capable of encapsulating the material such that the radon is enclosed within the additive. The additive material then prevents radon radiation from escaping through the additive, thus preventing someone working with the encapsulated material from being exposed to the dangerous radiation. Examples of chemical additives useful in the present invention include, but are not limited to, mineral oil, charcoal, activated carbon, silicates, sulfur, organic and inorganic polymers.

The amount of the additive material admixed with the radon-generating waste material is dependent on the type of waste material and the potential amount of radon contained within the waste material. In general, it is preferred that the amount of additive should at least be sufficient to encapsulate the radon existing in the waste material. Preferably, an excess amount of the additive is added to ensure that all of the radon remains encapsulated. Additionally, depending upon the types of waste, some wastes may contain more radon than other wastes. For example, since soil contains radium, wastes containing soil will have higher radon emissions. In general, the additive should be added in an amount of from about 0.1 to about 50 percent by weight of the waste material. More preferably, the amount of additive added is from about 10 to about 30 percent by weight of the waste material.

Radon has a half-life of 3.8 days. By slowing its movement through the matrix, less radon is emitted to the atmosphere. Methods to slow the movement may include adhering the radon to other particles or increasing the linear path to the environment. In operation, the additive material is admixed with the waste material in any known mixing device. The additive then surrounds and encapsulates any radon, thereby preventing alpha particles from escaping through the additive material. By "encapsulates" it is meant that the radon is substantially or totally enclosed within the chemical additive. Without the additive material, radon would pass through the waste material and any shielding material and into the environment where they could be inhaled by an individual working with the waste.

In a third embodiment of the present invention, the method comprises a combination of the first two embodiments. First, the radon-contaminated waste material is admixed with a chemical additive material designed to encapsulate the radon within the polymer. Next, the encapsulated waste material is admixed with a shielding material to incorporate the encapsulated waste within the matrix of the shielding material. Then, the admixture is formed into a geometric shape having a low surface area per unit volume.

Radon-generating waste materials which have been treated by any one of the previous embodiments may be further disposed of by any known means of disposal. However, one advantage of the chemical additive encapsulation embodiments is that these waste materials may, after the radon has been encapsulated, be used in building materials, especially when the shielding material is concrete. The waste material/shielding material admixture may be formed into slabs, or more preferably cubes, and used in buildings. Since the radon has been encapsulated, there is no problem with radon emissions thereby permitting these building materials to be used without causing harm to individuals contacting these building materials.

Optionally, in each of the above embodiments, a polymer sealant may be used as a further treatment step. The polymer sealant may be applied to the surface area of the radon-generating waste after the waste has been encapsulated within a chemical additive to provide an additional barrier against radon. Additionally, the polymer sealant may be applied to the surface of an admixture of radon-generating waste material and a shielding material, again as an additional barrier against radon.

The types of polymer sealants used are those which provide an effective barrier to radon emissions. Examples include sulfopolymer-acrylic copolymer blend emulsions, acrylic acid mixtures having a thixotropic agent, vinyl-acetate-ethylene copolymer mixtures having a thixotropic agent, and vinyl chloride copolymers having a thixotropic agent. These polymer sealants are added in an amount effective to thoroughly coat the surface area of the waste material or waste material/shielding material admixture such that any radon that may get to the surface area is prevented from escaping to the environment where they may harm an individual.

Those skilled in the art will recognize that the present invention is capable of many modifications and variations without departing from the scope thereof. Accordingly, the detailed description set forth above is meant to be illustrative only and are

not intended to limit, in any manner, the scope of the invention as set forth in the appended claims.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000